

# SERIE

# RE29.6

## PROFESSIONALE



- Distributore idraulico con valvole, leve a cloche e blocco di sicurezza
- Distribuidor hidraulico con valvulas, palancas de mando y bloqueo de seguridad
- Hydraulic distributor with valves, gearshift lever controls and safety lock
- Distributeur hydraulique avec soupapes, leviers à cloche et blocage de sureté



- Doppio martinetto di rotazione 180°, bloccaggio idraulico
- Duble martinete de rotacion 180°, bloqueo hidraulico
- Double cylinder for 180° rotation, hydraulic blocking
- Double vérin de rotation 180°, blocage hydraulique

### DOTAZIONI DI SERIE / CARATTERISTICAS SPECIFICATIONS / CARACTERISTIQUES

DOTAZIONI DI SERIE / CARATTERISTICAS SPECIFICATIONS / CARACTERISTIQUES		RE 29.6	
A	(mm)	A	(mm)
B	(mm)	B	(mm)
H	(mm)	H	(mm)
R	(mm)	R	(mm)
E	(mm)	E	(mm)
Forza di strappo al dente Fuerza de tiro al dente	(Kg)	Breakout capacity Force d'arrachement	(Kg)
Angolo di rotazione Angulo de rotación	(°)	Angle rotation Angle de rotation	(°)
Portata massima pompa Capacidad máx. de la bomba	(lt/min)	Pump max delivery Débit max pompe	(lt/min)
Capacità serbatoio Capacidad depósito	(lt)	Tank capacity Capacité du réservoir	(lt)
Benna scavo Cuchara excavación	(mm)	Digging bucket Benne d'excavation	(mm)
Peso Peso	(Kg)	Weight poids	(Kg)
Potenza trattore Potencia tractor	(hp)	Power requirements Puissance requise	(hp)
Larghezza telaio Bastidor	(mm)	Size frame Chassis	(mm)

